SKS IR SP

Plug-in coupling connector

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
compatible with	Pioneer
Additional feature	with ball valve
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	L (mm)	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 06 IR SP	6	G 1/4" -19	35,3	200,0	4	-25	110
SKS 10 IR SP	10	G 3/8" -19	38,0	200,0	4	-25	110
SKS 13 IR SP	12	G 1/2" -14	51,4	200,0	4	-25	125
SKS 20 IR SP	19	G 3/4" -14	46,0	200,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS SP	Dust protection coupling connector, SKS..SP

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.