

# SKS IR SP KE

Plug-in coupling connector

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>compatible with</b>	Pioneer
<b>Additional feature</b>	with plug valve
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Description

Plug-in couplings allow quick coupling.

## Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKS 06 IR SP KE</b>	6	G 1/4" -19	350,0	4	-25	125
<b>SKS 10 IR SP KE</b>	10	G 3/8" -19	300,0	4	-25	125
<b>SKS 13 IR SP KE</b>	12	G 1/2" -14	300,0	4	-25	125
<b>SKS 20 IR SP KE</b>	19	G 3/4" -14	250,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

<b>SKS ZUBS SP</b>	Dust protection coupling connector, SKS..SP
--------------------	---