

# SKS IR T

Plug-in coupling connector

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>compatible with</b>	Tema
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Description

Plug-in couplings allow quick coupling.  
For a high flow with minimal pressure loss.

## Ordering information

Other pressure and temperature figures available on request.

## Item

Identification	DN*	Size	Connecting thread	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)	Operating pressure (bar)
SKS 06 IR T	6	4	G 1/4" -19	2,5	-30	100	450,0
SKS 10 IR T	10	6	G 3/8" -19	3,0	-30	100	350,0
SKS 13 IR T	12	8	G 1/2" -14	3,0	-30	100	300,0
SKS 20 IR T	19	12	G 3/4" -14	2,5	-30	100	280,0
SKS 25 IR T	25	16	G 1" -11	3,5	-30	100	250,0

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

SKS ZUBS T Dust protection coupling connector, SKS..T