# SKS IR T

Plug-in coupling connector

## Properties

| | |
|---|---|
| **Application** | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| **Connection 1** | BSP cylindrical internal threads |
| **Sealing form 1** | for screw-in pins with shapes A, B and if necessary E |
| **compatible with** | Tema |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Description

Plug-in couplings allow quick coupling.
For a high flow with minimal pressure loss.

## Ordering information

Other pressure and temperature figures available on request.

## Item

| Identification | DN* | Size | Connecting thread | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) | Operating pressure (bar) |
|---|---|---|---|---|---|---|---|
| **SKS 06 IR T** | 6 | 4 | G 1/4" -19 | 2,5 | -30 | 100 | 450,0 |
| **SKS 10 IR T** | 10 | 6 | G 3/8" -19 | 3,0 | -30 | 100 | 350,0 |
| **SKS 13 IR T** | 12 | 8 | G 1/2" -14 | 3,0 | -30 | 100 | 300,0 |
| **SKS 20 IR T** | 19 | 12 | G 3/4" -14 | 2,5 | -30 | 100 | 280,0 |
| **SKS 25 IR T** | 25 | 16 | G 1" -11 | 3,5 | -30 | 100 | 250,0 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

| | |
|---|---|
| **SKS ZUBS T** | Dust protection coupling connector, SKS..T |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*