SKSS HL UDK / SKSS HS UDK

Plug-in coupling connector (bulkhead connection)

HANSA-FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Residual pressure:	Coupling under residual pressure is possible
Material	Steel
Surface	electro galvanised



Description

Plug-in couplings allow quick coupling.

Item

Identification	DN*	Series	for external pipe Ø (mm)	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKSS 06 HL 3 UDK	6	L	8	M 14x1,5	3	225,0	4	-25	125
SKSS 08 HL 3 UDK	8	L	10	M 16x1,5	3	225,0	4	-25	125
SKSS 10 HL 3 UDK	10	L	12	M 18x1,5	3	225,0	4	-25	125
SKSS 13 HL 3 UDK	12	L	15	M 22x1,5	3	225,0	4	-25	125
SKSS 16 HL 3 UDK	16	L	18	M 26x1,5	3	225,0	4	-25	125
SKSS 06 HS 3 UDK	6	S	10	M 18x1,5	3	225,0	4	-25	125
SKSS 08 HS 3 UDK	8	S	12	M 18x1,5	3	225,0	4	-25	125
SKSS 10 HS 3 UDK	10	S	14	M 22x1,5	3	225,0	4	-25	125
SKSS 13 HS 3 UDK	12	S	16	M 24x1,5	3	225,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Accessories

SKS ZUBS	Dust protection coupling connector, SKS..

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.