

# SKSS HL UDK / SKSS HS UDK

Plug-in coupling connector (bulkhead connection)

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Residual pressure:</b>	Coupling under residual pressure is possible
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Description

Plug-in couplings allow quick coupling.

## Item

Identification	DN*	Series	for external pipe Ø (mm)	Connecting thread	Size	Operating pres- sure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKSS 06 HL 3 UDK	6	L	8	M 14x1,5	3	225,0	4	-25	125
SKSS 08 HL 3 UDK	8	L	10	M 16x1,5	3	225,0	4	-25	125
SKSS 10 HL 3 UDK	10	L	12	M 18x1,5	3	225,0	4	-25	125
SKSS 13 HL 3 UDK	12	L	15	M 22x1,5	3	225,0	4	-25	125
SKSS 16 HL 3 UDK	16	L	18	M 26x1,5	3	225,0	4	-25	125
SKSS 06 HS 3 UDK	6	S	10	M 18x1,5	3	225,0	4	-25	125
SKSS 08 HS 3 UDK	8	S	12	M 18x1,5	3	225,0	4	-25	125
SKSS 10 HS 3 UDK	10	S	14	M 22x1,5	3	225,0	4	-25	125
SKSS 13 HS 3 UDK	12	S	16	M 24x1,5	3	225,0	4	-25	125

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Accessories

**SKS ZUBS** Dust protection coupling connector, SKS..