HANSA/FLEX

Properties

| Material | Brass | | |
|--------------|--------------------|--|--|
| O-ring | Viton, PTFE coated | | |
| Connection 1 | Hose connection | | |
| • | | | |



Ordering information

Other pressure and temperature figures available on request.

| Item | | | | | | | |
|--------------------|-----|-----------------|---------------------|--------------------|-----------|---------------------------|---------------------------|
| Identification | DN* | Hose connection | Connector dimension | Operating pressure | SF coup.* | Mineral oil temp. min. | Mineral oil temp. max. |
| | | (mm) | (mm) | (bar) | | (°C) | (°C) |
| TKM 09 OV 06 MM ND | 6 | 6 | 9 | 15,0 | 3 | -15 | 150 |
| TKM 09 OV 10 MM ND | 10 | 10 | 9 | 15,0 | 3 | -15 | 150 |
| TKM 13 OV 10 MM ND | 10 | 10 | 13 | 15,0 | 3 | -15 | 150 |
| TKM 13 OV 13 MM ND | 12 | 13 | 13 | 15,0 | 3 | -15 | 150 |
| TKM 19 OV 16 MM ND | 16 | 16 | 19 | 15,0 | 3 | -15 | 150 |
| TKM 19 OV 19 MM ND | 19 | 19 | 19 | 15,0 | 3 | -15 | 150 |

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled