TKS OV HB

Temperature control coupling connector without valve

Properties

Connection 1	BSP external thread, cylindrical
Sealing form 1	60° inner cone
Material	Brass



Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Connector dimension (mm)	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)	AF (mm)
TKS 09 OV 02 HB	2	G 1/8" -28	9	15,0	3	-15	150	11
TKS 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	15
TKS 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	17
TKS 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	15
TKS 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	17
TKS 13 OV 13 HB	12	G 1/2" -14	13	15,0	3	-15	150	22
TKS 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	22
TKS 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	27

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled – AF = Width across flats

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.