

# TKS OV HB

Temperature control coupling connector without valve



## Properties

**Connection 1** BSP external thread, cylindrical

**Sealing form 1** 60° inner cone

**Material** Brass



## Ordering information

Other pressure and temperature figures available on request.

Item								
Identification	DN*	Connecting thread	Connector dimension (mm)	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)	AF (mm)
TKS 09 OV 02 HB	2	G 1/8" -28	9	15,0	3	-15	150	11
TKS 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	15
TKS 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	17
TKS 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	15
TKS 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	17
TKS 13 OV 13 HB	12	G 1/2" -14	13	15,0	3	-15	150	22
TKS 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	22
TKS 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	27

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled – AF = Width across flats