TKS OV ROR

Temperature control coupling connector without valve

Properties

Connection 1	Pipe socket to be cut into sections
Material	Brass



Ordering information

Other pressure and temperature figures available on request.

Item

Identification	External pipe Ø (mm)	Connector dimension (mm)	Length (mm)	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)	AF (mm)
TKS 09 OV ROR 08 L 68	8	9	68	15,0	3	-15	150	9
TKS 09 OV ROR 08 L 100	8	9	100	15,0	3	-15	150	9
TKS 09 OV ROR 10 L 120	10	9	120	15,0	3	-15	150	11
TKS 09 OV ROR 10 L 240	10	9	240	15,0	3	-15	150	11
TKS 09 OV ROR 10 L 360	10	9	360	15,0	3	-15	150	11
TKS 13 OV ROR 14 L 150	14	13	150	15,0	3	-15	150	15
TKS 13 OV ROR 14 L 300	14	13	300	15,0	3	-15	150	15

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled – AF = Width across flats

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.