

# PA 500 AOB 45 VA

Swage fitting, DKOR angle 45°

## Properties

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Application</b>     | Swage fitting for HD 500 hoses       |
| <b>Connection 1</b>    | BSP nut thread                       |
| <b>Sealing form 1</b>  | 60° outer cone with O-ring           |
| <b>Short code</b>      | DKOR                                 |
| <b>Standard</b>        | ISO 8434-6<br>BS 5200                |
| <b>Integration</b>     | with pull-out protection (interlock) |
| <b>Scope of supply</b> | Swage nipple + swage ferrule         |
| <b>Material</b>        | Stainless steel                      |



## Ordering information

Seals of NBR  
FPM (Viton) on request

| Item             |    |      |        |            |    |            |
|------------------|----|------|--------|------------|----|------------|
| Identification   | DN | Size | Inches | L2<br>(mm) | S1 | OR         |
| PA 520 AOB 45 VA | 19 | 12   | 3/4"   | 39,0       | 32 | 17.1 x 1.6 |
| PA 525 AOB 45 VA | 25 | 16   | 1"     | 46,0       | 41 | 22.1 x 1.6 |
| PA 532 AOB 45 VA | 31 | 20   | 1.1/4" | 52,0       | 50 | 29.1 x 1.6 |
| PA 540 AOB 45 VA | 38 | 24   | 1.1/2" | 49,0       | 60 | 35.1 x 1.6 |
| PA 550 AOB 45 VA | 51 | 32   | 2"     | 81,0       | 70 | 48.1 x 1.6 |

## Product versions

PA 500 AOB 45 A Swage fitting, DKOR angle 45°, Steel