# PA 500 AOB VA

Swage fitting, DKOR

# HANSA/FLEX

## Properties

| Application     | Swage fitting for HD 500 hoses       |  |  |  |  |
|-----------------|--------------------------------------|--|--|--|--|
| Connection 1    | BSP nut thread                       |  |  |  |  |
| Sealing form 1  | 60° outer cone with O-ring           |  |  |  |  |
| Short code      | DKOR                                 |  |  |  |  |
| Standard        | ISO 8434-6<br>BS 5200                |  |  |  |  |
| Integration     | with pull-out protection (interlock) |  |  |  |  |
| Scope of supply | Swage nipple + swage ferrule         |  |  |  |  |
| Material        | Stainless steel                      |  |  |  |  |





#### Item

| Identification | DN | Size | Inches | G1           | S1 | OR         |  |
|----------------|----|------|--------|--------------|----|------------|--|
| PA 520 AOB VA  | 19 | 12   | 3/4"   | G 3/4" -14   | 32 | 17.1 x 1.6 |  |
| PA 525 AOB VA  | 25 | 16   | 1"     | G 1" -11     | 41 | 22.1 x 1.6 |  |
| PA 532 AOB VA  | 31 | 20   | 1.1/4" | G 1.1/4" -11 | 50 | 29.1 x 1.6 |  |
| PA 540 AOB VA  | 38 | 24   | 1.1/2" | G 1.1/2" -11 | 60 | 35.1 x 1.6 |  |
| PA 550 AOB VA  | 51 | 32   | 2"     | G 2" -11     | 70 | 48.1 x 1.6 |  |

### **Product versions**

PA 500 AOB A Swage fitting, DKOR, Steel