

# PA 500 AOS 90 VA

Swage fitting, DKOS angle 90°

## Properties

<b>Application</b>	Swage fitting for HD 500 hoses
<b>Connection 1</b>	metric nut thread
<b>Sealing form 1</b>	24° outer cone with O-ring
<b>Short code</b>	DKOS
<b>Standard</b>	ISO 8434-1
<b>Integration</b>	with pull-out protection (interlock)
<b>Scope of supply</b>	Swage nipple + swage ferrule
<b>Material</b>	Stainless steel



## Ordering information

Seals of NBR  
FPM (Viton) on request

Item									
Identification	DN	Size	Inches	G1	for external pipe Ø (mm)	L2 (mm)	S1	OR	
PA 520 AOS 16 90 VA	19	16	3/4"	M 30 x 2	20	83,0	36	16.0 x 2.5	
PA 520 AOS 90 VA	19	16	3/4"	M 36 x 2	25	76,0	46	20.0 x 2.5	
PA 525 AOS 20 90 VA	25	16	1"	M 36 x 2	25	95,5	46	20.0 x 2.5	
PA 525 AOS 90 VA	25	16	1"	M 42 x 2	30	83,0	50	25.0 x 2.5	
PA 532 AOS 90 VA	31	20	1.1/4"	M 52 x 2	38	101,0	60	33.0 x 2.5	

## Product versions

PA 500 AOS A Swage fitting, DKOS, Steel