

PA 500 SF 45 VA

Swage fitting, SFL angle 45°

Properties

| | |
|------------------------|--------------------------------------|
| Application | Swage fitting for HD 500 hoses |
| Connection 1 | SAE flange connection 3000 PSI |
| Sealing form 1 | flat seal with SF O-ring |
| Short code | SFL |
| Standard | SAE J518 ISO 6162-1 |
| Integration | with pull-out protection (interlock) |
| Scope of supply | Swage nipple + swage ferrule |
| Material | Stainless steel |



Ordering information

Seals of NBR
FPM (Viton) on request

Item

| Identification | DN | Size | Inches | Flange size | D (mm) | H (mm) | L2 (mm) |
|--------------------|----|------|--------|-------------|-----------|-----------|------------|
| PA 520 SF 45 VA | 19 | 12 | 3/4" | 3/4" | 38,1 | 6,7 | 38,0 |
| PA 520 SF 25 45 VA | 19 | 12 | 3/4" | 1" | 44,5 | 8,0 | 39,5 |
| PA 525 SF 45 VA | 25 | 16 | 1" | 1" | 44,5 | 8,0 | 39,0 |
| PA 525 SF 32 45 VA | 25 | 16 | 1" | 1.1/4" | 50,8 | 8,0 | 44,0 |
| PA 532 SF 45 VA | 31 | 20 | 1.1/4" | 1.1/4" | 50,8 | 8,0 | 45,0 |
| PA 532 SF 40 45 VA | 31 | 20 | 1.1/4" | 1.1/2" | 60,3 | 8,0 | 46,0 |
| PA 540 SF 45 VA | 38 | 24 | 1.1/2" | 1.1/2" | 60,3 | 8,0 | 49,0 |
| PA 540 SF 50 45 VA | 38 | 24 | 1.1/2" | 2" | 71,4 | 9,5 | 60,0 |
| PA 550 SF 45 VA | 51 | 32 | 2" | 2" | 71,4 | 9,5 | 65,0 |

Product versions

PA 500 SF 45 A Swage fitting, SFL angle 45°, Steel