

ND AOL

Plug-in nipple, DKOL

HANSA FLEX

Properties

| | |
|-----------------------|----------------------------|
| Connection 1 | metric nut thread |
| Sealing form 1 | 24° outer cone with O-ring |
| Short code | DKOL |
| Standard | ISO 8434-1 |
| Material | Steel |
| Surface | electro galvanised |



Note

Undamaged nipples can be reused.

Item

| Identification | DN | Size | Inches | G1 | for external pipe Ø (mm) | L1 (mm) | S1 | OR |
|----------------|----|------|--------|------------|-----------------------------|------------|----|------------|
| ND 06 AOL 04 | 6 | 4 | 1/4" | M 12 x 1.5 | 6 | 40,0 | 14 | 4.5 x 1.5 |
| ND 06 AOL | 6 | 4 | 1/4" | M 14 x 1.5 | 8 | 36,0 | 17 | 6.5 x 1.5 |
| ND 06 AOL 08 | 6 | 4 | 1/4" | M 16 x 1.5 | 10 | 36,0 | 19 | 8.5 x 1.5 |
| ND 10 AOL 08 | 10 | 6 | 3/8" | M 16 x 1.5 | 10 | 40,0 | 19 | 8.5 x 1.5 |
| ND 10 AOL | 10 | 6 | 3/8" | M 18 x 1.5 | 12 | 40,0 | 22 | 10.5 x 1.5 |
| ND 13 AOL | 12 | 8 | 1/2" | M 22 x 1.5 | 15 | 44,0 | 27 | 12.5 x 1.5 |
| ND 16 AOL | 16 | 10 | 5/8" | M 26 x 1.5 | 18 | 56,0 | 32 | 16.0 x 2.0 |
| ND 20 AOL | 19 | 12 | 3/4" | M 30 x 2 | 22 | 58,0 | 36 | 20.0 x 2.0 |

Accessories

ND ASR GE, RO, BL Stop ring for plug-in nipple