


| Properties | | | | | |
|----------------|-------------------------------|--|--|--|--|
| Connection 1 | Banjo for metric hollow screw | | | | |
| Sealing form 1 | Sealed by copper ring | | | | |
| Connection 2 | Hose connection | | | | |
| Short code | RGN | | | | |
| Standard | DIN 7642 | | | | |
| Material | Steel | | | | |
| Surface | electro galvanised | | | | |





Note

Undamaged nipples can be reused.

| Item | | | | | | |
|----------------|----|------|--------|------------|------------------|------------|
| Identification | DN | Size | Inches | D1 (mm) | for hollow screw | L1 (mm) |
| ND 06 B 02 | 6 | 4 | 1/4" | 8,1 | M 8 | 36,0 |
| ND 06 B 04 | 6 | 4 | 1/4" | 10,1 | M 10 | 38,0 |
| ND 06 B | 6 | 4 | 1/4" | 12,1 | M 12 | 40,0 |
| ND 06 B 08 | 6 | 4 | 1/4" | 14,1 | M 14 | 42,0 |
| ND 10 B 06 | 10 | 6 | 3/8" | 12,1 | M 12 | 44,0 |
| ND 10 B 08 | 10 | 6 | 3/8" | 14,1 | M 14 | 47,0 |
| ND 10 B | 10 | 6 | 3/8" | 16,1 | M 16 | 49,0 |
| ND 13 B 08 | 12 | 8 | 1/2" | 14,1 | M 14 | 51,0 |
| ND 13 B 16 | 12 | 8 | 1/2" | 22,1 | M 22 | 58,0 |
| ND 16 B | 16 | 10 | 5/8" | 22,1 | M 22 | 68,0 |

Accessories

ND ASR GE, RO, BL Stop ring for plug-in nipple