
PA 500 AJF 90 A

Swage fitting, ORFS angle 90°



| D | | | | | | |
|-----------------|--------------------------------------|--|--|--|--|--|
| Properties | | | | | | |
| Application | Swage fitting for HD 500 hoses | | | | | |
| Connection 1 | UN/UNF nut threads | | | | | |
| Sealing form 1 | flat sealing | | | | | |
| Short code | ORFS | | | | | |
| Standard | ISO 8434-3 | | | | | |
| Integration | with pull-out protection (interlock) | | | | | |
| Scope of supply | Swage nipple + swage ferrule | | | | | |
| Material | Steel | | | | | |
| Surface | electro galvanised | | | | | |
| | | | | | | |





| Item | | | | | | | | | | |
|-----------------|----|------|--------|--------------------|-----------------|------------|------------|----|--|--|
| Identification | DN | Size | Inches | Operating pressure | G1 | L1 (mm) | L2 (mm) | S1 | | |
| PA 720 AJF 90 | 19 | 12 | 3/4" | 413,0 | 1.3/16" -12 UN | 126,0 | 56,0 | 36 | | |
| PA 725 AJF 90 | 25 | 16 | 1" | 413,0 | 1.7/16" -12 UN | 157,5 | 68,0 | 41 | | |
| PA 532 AJF 90 A | 31 | 20 | 1.1/4" | 275,0 | 1.11/16" -12 UN | 178,0 | 34,0 | 50 | | |
| PA 540 AJF 90 A | 38 | 24 | 1.1/2" | 275,0 | 2" -12 UN | 209,0 | 32,0 | 60 | | |