

# PA 500 AOB A

Swage fitting, DKOR

**HANSA FLEX**

## Properties

<b>Application</b>	Swage fitting for HD 500 hoses
<b>Connection 1</b>	BSP nut thread
<b>Sealing form 1</b>	60° outer cone with O-ring
<b>Short code</b>	DKOR
<b>Standard</b>	ISO 8434-6 BS 5200
<b>Integration</b>	with pull-out protection (interlock)
<b>Scope of supply</b>	Swage nipple + swage ferrule
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	DN	Size	Inches	G1	L1 (mm)	S1	OR
PA 720 AOB	19	12	3/4"	G 3/4" -14	88,0	32	17.1 x 1.6
PA 725 AOB	25	16	1"	G 1" -11	102,5	41	22.1 x 1.6
PA 532 AOB A	31	20	1.1/4"	G 1.1/4" -11	116,0	50	29.1 x 1.6
PA 540 AOB A	38	24	1.1/2"	G 1.1/2" -11	133,5	55	35.1 x 1.6
PA 550 AOB A	51	32	2"	G 2" -11	147,0	70	48.1 x 1.6

## Product versions

PA 500 AOB VA	Swage fitting, DKOR, Stainless steel
---------------	--------------------------------------