

# PA 500 AOJ 45 A

Swage fitting, DKOJ angle 45°

## Properties

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Application</b>     | Swage fitting for HD 500 hoses       |
| <b>Connection 1</b>    | UN/UNF nut threads                   |
| <b>Sealing form 1</b>  | 74° inner cone with O-ring           |
| <b>Short code</b>      | DKOJ                                 |
| <b>Standard</b>        | ISO 8434-2                           |
| <b>Integration</b>     | with pull-out protection (interlock) |
| <b>Scope of supply</b> | Swage nipple + swage ferrule         |
| <b>Material</b>        | Steel                                |
| <b>Surface</b>         | electro galvanised                   |



## Item

| Identification  | DN | Size | Inches | Operating pressure (bar) | G1             | L1 (mm) | L2 (mm) | S1 | OR           |
|-----------------|----|------|--------|--------------------------|----------------|---------|---------|----|--------------|
| PA 720 AOJ 45   | 19 | 12   | 3/4"   | -                        | 1.1/16" -12 UN | 140,0   | 34,5    | 32 | 19.00 x 1.50 |
| PA 725 AOJ 45   | 25 | 16   | 1"     | -                        | 1.5/16" -12 UN | 169,5   | 39,0    | 41 | 25.00 x 1.50 |
| PA 532 AOJ 45 A | 31 | 20   | 1.1/4" | 420,0                    | 1.5/8" -12 UN  | 199,0   | 49,5    | 50 | 31.47 x 1.78 |
| PA 540 AOJ 45 A | 38 | 24   | 1.1/2" | 420,0                    | 1.7/8" -12 UN  | 233,0   | 58,0    | 55 | 37.82 x 1.78 |
| PA 550 AOJ 45 A | 51 | 32   | 2"     | 345,0                    | 2.1/2" -12 UN  | 275,0   | 64,0    | 75 | 50.00 x 2.00 |