
PA 500 AOJ A

Swage fitting, DKOJ

Properties

Application	Swage fitting for HD 500 hoses
Connection 1	UN/UNF nut threads
Sealing form 1	74° inner cone with O-ring
Short code	DKOJ
Standard	ISO 8434-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised





Item

Identification	DN	Size	Inches	Operating pressure (bar)	G1	L1 (mm)	S1	OR
PA 720 AOJ	19	12	3/4"	420,0	1.1/16" -12 UN	90,0	32	19.00 x 1.50
PA 725 AOJ	25	16	1"	420,0	1.5/16" -12 UN	103,5	41	25.00 x 1.50
PA 532 AOJ A	31	20	1.1/4"	420,0	1.5/8" -12 UN	115,0	50	31.47 x 1.78
PA 540 AOJ A	38	24	1.1/2"	420,0	1.7/8" -12 UN	132,0	55	37.82 x 1.78
PA 550 AOJ A	51	32	2"	345,0	2.1/2" -12 UN	146,0	75	50.00 x 2.00

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.