
## PA 500 AOS 45 A

Swage fitting, DKOS angle 45°



| Properties      |                                      |  |  |  |  |  |
|-----------------|--------------------------------------|--|--|--|--|--|
| Application     | Swage fitting for HD 500 hoses       |  |  |  |  |  |
| Connection 1    | metric nut thread                    |  |  |  |  |  |
| Sealing form 1  | 24° outer cone with O-ring           |  |  |  |  |  |
| Short code      | DKOS                                 |  |  |  |  |  |
| Standard        | ISO 8434-1                           |  |  |  |  |  |
| Integration     | with pull-out protection (interlock) |  |  |  |  |  |
| Scope of supply | Swage nipple + swage ferrule         |  |  |  |  |  |
| Material        | Steel                                |  |  |  |  |  |
| Surface         | electro galvanised                   |  |  |  |  |  |
|                 |                                      |  |  |  |  |  |





| Item               |    |      |        |          |                     |            |            |    |            |
|--------------------|----|------|--------|----------|---------------------|------------|------------|----|------------|
| Identification     | DN | Size | Inches | G1       | for external pipe Ø | L1<br>(mm) | L2<br>(mm) | S1 | OR         |
| PA 720 AOS 16 45   | 19 | 12   | 3/4"   | M 30 x 2 | 20                  | 133,0      | 27,0       | 36 | 16.0 x 2.5 |
| PA 720 AOS 45      | 19 | 12   | 3/4"   | M 36 x 2 | 25                  | 136,0      | 30,0       | 46 | 20.0 x 2.5 |
| PA 720 AOS 25 45   | 19 | 12   | 3/4"   | M 42 x 2 | 30                  | 142,0      | 35,0       | 50 | 27.0 x 2.5 |
| PA 725 AOS 20 45   | 25 | 16   | 1"     | M 36 x 2 | 25                  | 156,5      | 34,5       | 41 | 22.0 x 2.5 |
| PA 725 AOS 45      | 25 | 16   | 1"     | M 42 x 2 | 30                  | 164,0      | 34,5       | 50 | 25.0 x 2.5 |
| PA 725 AOS 32 45   | 25 | 16   | 1"     | M 52 x 2 | 38                  | 170,0      | 41,0       | 60 | 33.0 x 2.5 |
| PA 532 AOS 25 45 A | 31 | 20   | 1"     | M 42 x 2 | 30                  | 175,0      | 39,5       | 50 | 27.0 x 2.5 |
| PA 532 AOS 45 A    | 31 | 20   | 1.1/4" | M 52 x 2 | 38                  | 192,5      | 41,0       | 60 | 33.0 x 2.5 |

| <b>Product versions</b> |   |           |
|-------------------------|---|-----------|
| DA 500 400 45 1/4       | _ | <br>D1/00 |

PA 500 AOS 45 VA Swage fitting, DKOS angle 45°, Stainless steel