

# PA 500 HJ A

Swage fitting, AGJ

**HANSA FLEX**

## Properties

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Application</b>     | Swage fitting for HD 500 hoses       |
| <b>Connection 1</b>    | UN/UNF external threads              |
| <b>Sealing form 1</b>  | 74° outer cone                       |
| <b>Short code</b>      | AGJ                                  |
| <b>Standard</b>        | ISO 8434-2                           |
| <b>Integration</b>     | with pull-out protection (interlock) |
| <b>Scope of supply</b> | Swage nipple + swage ferrule         |
| <b>Material</b>        | Steel                                |
| <b>Surface</b>         | electro galvanised                   |



## Item

| Identification | DN | Size | Inches | G1             | L1 (mm) | S1 |
|----------------|----|------|--------|----------------|---------|----|
| PA 720 HJ      | 19 | 12   | 3/4"   | 1.1/16" -12 UN | 102,5   | 27 |
| PA 725 HJ      | 25 | 16   | 1"     | 1.5/16" -12 UN | 117,0   | 36 |
| PA 532 HJ A    | 31 | 20   | 1.1/4" | 1.5/8" -12 UN  | 127,0   | 46 |
| PA 540 HJ A    | 38 | 24   | 1.1/2" | 1.7/8" -12 UN  | 145,5   | 50 |
| PA 550 HJ A    | 51 | 32   | 2"     | 2.1/2" -12 UN  | 169,5   | 65 |

## Product versions

|              |                                     |
|--------------|-------------------------------------|
| PA 500 HJ VA | Swage fitting, AGJ, Stainless steel |
|--------------|-------------------------------------|