

# PA 500 SF 90 A

Swage fitting, SFL angle 90°

## Properties

<b>Application</b>	Swage fitting for HD 500 hoses
<b>Connection 1</b>	SAE flange connection 3000 PSI
<b>Sealing form 1</b>	flat seal with SF O-ring
<b>Short code</b>	SFL
<b>Standard</b>	SAE J518 ISO 6162-1
<b>Integration</b>	with pull-out protection (interlock)
<b>Scope of supply</b>	Swage nipple + swage ferrule
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



Item									
Identification	DN	Size	Inches	Flange size	D (mm)	H (mm)	L1 (mm)	L2 (mm)	
PA 720 SF 90	19	12	3/4"	3/4"	38,1	6,8	127,5	58,0	
PA 720 SF 25 90	19	12	3/4"	1"	44,5	8,1	127,5	61,0	
PA 725 SF 20 90	25	16	1"	3/4"	38,1	6,8	144,0	64,5	
PA 725 SF 90	25	16	1"	1"	44,5	8,1	158,0	67,0	
PA 725 SF 32 90	25	16	1"	1.1/4"	50,8	8,1	158,0	69,5	
PA 532 SF 25 90 A	31	20	1.1/4"	1"	44,5	8,0	162,0	76,0	
PA 532 SF 90 A	31	20	1.1/4"	1.1/4"	50,8	8,0	181,0	79,5	
PA 532 SF 40 90 A	31	20	1.1/4"	1.1/2"	60,3	8,0	182,0	86,7	
PA 540 SF 32 90 A	38	24	1.1/2"	1.1/4"	50,8	8,0	193,0	94,0	
PA 540 SF 90 A	38	24	1.1/2"	1.1/2"	60,3	8,0	211,0	99,0	
PA 540 SF 50 90 A	38	24	1.1/2"	2"	71,4	9,5	218,0	100,0	
PA 550 SF 90 A	51	32	2"	2"	71,4	9,5	250,0	112,5	

## Product versions

PA 500 SF 90 VA Swage fitting, SFL angle 90°, Stainless steel