

PA 500 SF6 A

Swage fitting, SFS

HANSA FLEX

Properties

Application	Swage fitting for HD 500 hoses
Connection 1	SAE flange connection 6000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFS
Standard	SAE J518 ISO 6162-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised



Item

Identification	DN	Size	Inches	Flange size	D (mm)	H (mm)	L1 (mm)
PA 720 SF6	19	12	3/4"	3/4"	41,3	8,8	124,5
PA 720 SF6 25	19	12	3/4"	1"	47,6	9,6	129,0
PA 725 SF6 20	25	16	1"	3/4"	41,3	8,8	134,0
PA 725 SF6	25	16	1"	1"	47,6	9,6	146,5
PA 725 SF6 32	25	16	1"	1.1/4"	54,0	10,4	151,0
PA 532 SF6 25 A	31	20	1.1/4"	1"	47,6	9,6	149,0
PA 532 SF6 A	31	20	1.1/4"	1.1/4"	54,0	10,4	162,5
PA 532 SF6 40 A	31	20	1.1/4"	1.1/2"	63,5	12,7	167,0
PA 540 SF6 32 A	38	24	1.1/2"	1.1/4"	54,0	10,4	162,0
PA 540 SF6 A	38	24	1.1/2"	1.1/2"	63,5	12,7	183,5
PA 540 SF6 50 A	38	24	1.1/2"	2"	79,4	12,7	188,0
PA 550 SF6 A	51	32	2"	2"	79,4	12,7	202,0

Product versions

PA 500 SF6 VA Swage fitting, SFS, Stainless steel