
## PA 600 SF6 45 VA

Swage fitting, SFS angle 45°



| Properties      |                                      |  |  |  |
|-----------------|--------------------------------------|--|--|--|
| Application     | Swage fitting for HD 600 hoses       |  |  |  |
| Connection 1    | SAE flange connection 6000 PSI       |  |  |  |
| Sealing form 1  | flat seal with SF O-ring             |  |  |  |
| Short code      | SFS                                  |  |  |  |
| Standard        | SAE J518<br>ISO 6162-2               |  |  |  |
| Integration     | with pull-out protection (interlock) |  |  |  |
| Scope of supply | Swage nipple + swage ferrule         |  |  |  |
| Material        | Stainless steel                      |  |  |  |





## Ordering information

Seals of NBR

FPM (Viton) on request

| Item             |    |      |        |             |      |      |      |  |
|------------------|----|------|--------|-------------|------|------|------|--|
| Identification   | DN | Size | Inches | Flange size | D    | Н    | L2   |  |
|                  |    |      |        |             | (mm) | (mm) | (mm) |  |
| PA 650 SF6 45 VA | 51 | 32   | 2"     | 2"          | 79,4 | 12,6 | 65,0 |  |

| Product versions |                                     |  |  |
|------------------|-------------------------------------|--|--|
| PA 600 SF6 45    | Swage fitting, SFS angle 45°, Steel |  |  |