
PA 700 AOS 90 VA

Swage fitting, DKOS angle 90°



| Properties | | | | | |
|-----------------|--------------------------------------|--|--|--|--|
| Application | Swage fitting for HD 700 hoses | | | | |
| Connection 1 | metric nut thread | | | | |
| Sealing form 1 | 24° outer cone with O-ring | | | | |
| Short code | DKOS | | | | |
| Standard | ISO 8434-1 | | | | |
| Integration | with pull-out protection (interlock) | | | | |
| Scope of supply | Swage nipple + swage ferrule | | | | |
| Material | Stainless steel | | | | |





Ordering information

Seals of NBR

FPM (Viton) on request

| ltem | | | | | | | | | | |
|---------------------|----|------|--------|----------|---------------------|------------|----|------------|--|--|
| Identification | DN | Size | Inches | G1 | for external pipe Ø | L2 (mm) | S1 | OR | | |
| PA 720 AOS 16 90 VA | 19 | 12 | 3/4" | M 30 x 2 | 20 | 83,0 | 36 | 20.0 x 2.5 | | |
| PA 720 AOS 90 VA | 19 | 12 | 3/4" | M 36 x 2 | 25 | 76,0 | 46 | 22.0 x 2.5 | | |
| PA 725 AOS 90 VA | 25 | 16 | 1" | M 42 x 2 | 30 | 83,0 | 50 | 25.0 x 2.5 | | |
| PA 732 AOS 90 VA | 31 | 20 | 1.1/4" | M 52 x 2 | 38 | 101,0 | 60 | 33.0 x 2.5 | | |

Product versions PA 700 AOS 90