

PA 700 SF6 90 VA

Swage fitting, SFS angle 90°

HANSA FLEX

Properties

Application	Swage fitting for HD 700 hoses
Connection 1	SAE flange connection 6000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFS
Standard	SAE J518 ISO 6162-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Stainless steel



Ordering information

Seals of NBR

FPM (Viton) on request

Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)	L2 (mm)
PA 720 SF6 90 VA	19	12	3/4"	3/4"	420,0	41,3	8,8	71,0
PA 725 SF6 90 VA	25	16	1"	1"	420,0	47,6	9,5	77,0
PA 732 SF6 90VA	31	20	1.1/4"	1.1/4"	420,0	54,0	10,3	93,5
PA 732 SF6 40 90 VA	31	20	1.1/4"	1.1/2"	420,0	63,5	12,6	96,0
PA 740 SF6 90 VA	38	24	1.1/2"	1.1/2"	420,0	63,5	12,6	107,0
PA 740 SF6 50 90 VA	38	24	1.1/2"	2"	420,0	79,4	12,6	121,5

Product versions

PA 600 SF6 90 Swage fitting, SFS angle 90°, Steel