

# PA 700 SF6 VA

Swage fitting, SFS

**HANSA FLEX**

## Properties

|                        |                                      |
|------------------------|--------------------------------------|
| <b>Application</b>     | Swage fitting for HD 700 hoses       |
| <b>Connection 1</b>    | SAE flange connection 6000 PSI       |
| <b>Sealing form 1</b>  | flat seal with SF O-ring             |
| <b>Short code</b>      | SFS                                  |
| <b>Standard</b>        | SAE J518<br>ISO 6162-2               |
| <b>Integration</b>     | with pull-out protection (interlock) |
| <b>Scope of supply</b> | Swage nipple + swage ferrule         |
| <b>Material</b>        | Stainless steel                      |



## Ordering information

Seals of NBR

FPM (Viton) on request

## Item

| Identification   | DN | Size | Inches | Flange size | Operating pressure<br>(bar) | D<br>(mm) | H<br>(mm) |
|------------------|----|------|--------|-------------|-----------------------------|-----------|-----------|
| PA 720 SF6 VA    | 19 | 12   | 3/4"   | 3/4"        | 420,0                       | 41,3      | 8,8       |
| PA 720 SF6 25 VA | 19 | 12   | 3/4"   | 1"          | 420,0                       | 47,6      | 9,5       |
| PA 725 SF6 VA    | 25 | 16   | 1"     | 1"          | 420,0                       | 47,6      | 9,5       |
| PA 732 SF6 VA    | 31 | 20   | 1.1/4" | 1.1/4"      | 420,0                       | 54,0      | 10,3      |
| PA 732 SF6 40 VA | 31 | 20   | 1.1/4" | 1.1/2"      | 420,0                       | 63,5      | 12,6      |
| PA 740 SF6 VA    | 38 | 24   | 1.1/2" | 1.1/2"      | 420,0                       | 63,5      | 12,6      |
| PA 740 SF6 50 VA | 38 | 24   | 1.1/2" | 2"          | 420,0                       | 79,4      | 12,6      |

## Product versions

PA 700 SF6 Swage fitting, SFS, Steel