
PA 700 SF6 VA

Swage fitting, SFS

Properties

Application	Swage fitting for HD 700 hoses
Connection 1	SAE flange connection 6000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFS
Standard	SAE J518 ISO 6162-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Stainless steel





Ordering information

Seals of NBR

FPM (Viton) on request

Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)
PA 720 SF6 VA	19	12	3/4"	3/4"	420,0	41,3	8,8
PA 720 SF6 25 VA	19	12	3/4"	1"	420,0	47,6	9,5
PA 725 SF6 VA	25	16	1"	1"	420,0	47,6	9,5
PA 732 SF6 VA	31	20	1.1/4"	1.1/4"	420,0	54,0	10,3
PA 732 SF6 40 VA	31	20	1.1/4"	1.1/2"	420,0	63,5	12,6
PA 740 SF6 VA	38	24	1.1/2"	1.1/2"	420,0	63,5	12,6
PA 740 SF6 50 VA	38	24	1.1/2"	2"	420,0	79,4	12,6

Product versions

PA 700 SF6	Swage fitting, SFS, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.