PAY 300 AJ


Swage fitting, DKJ

HANSA-FLEX

Properties

Connection 1	UN/UNF nut threads
Sealing form 1	74° inner cone
Short code	DKJ
Standard	ISO 8434-2
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised





Item

Identification	DN	Size	Inches	G1	L1 (mm)	S1
PAY 306 AJ	6	4	1/4"	7/16"-20 UNF	-	-
PAY 306 AJ 08	6	4	1/4"	1/2"-20 UNF	55,0	19
PAY 310 AJ	10	6	3/8"	9/16"-18 UNF	59,0	22
PAY 310 AJ 13	10	6	3/8"	3/4"-16 UNF	59,0	24
PAY 313 AJ	12	8	1/2"	3/4"-16 UNF	64,0	27
PAY 313 AJ 16	12	8	1/2"	7/8" -14 UNF	62,0	27
PAY 316 AJ	16	10	5/8"	7/8" -14 UNF	73,0	27
PAY 320 AJ	19	12	3/4"	1.1/16" -12 UN	79,0	36
PAY 325 AJ	25	16	1"	1.5/16" -12 UN	77,0	41
PAY 325 AJ 32	25	16	1"	1.5/8" -12 UN	75,0	50
PAY 332 AJ	31	20	1.1/4"	1.5/8" -12 UN	-	-

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.