


| Properties | | | | | |
|-----------------|---------------------------------|--|--|--|--|
| Connection 1 | metric cylindrical outer thread | | | | |
| Sealing form 1 | 24° inner cone | | | | |
| Short code | CES | | | | |
| Standard | ISO 8434-1 | | | | |
| Scope of supply | Swage nipple + swage ferrule | | | | |
| Material | Steel | | | | |
| Surface | electro galvanised | | | | |





| Item | | | | | | | | |
|----------------|----|------|--------|------------|---------------------|------------|----|--|
| Identification | DN | Size | Inches | G1 | for external pipe Ø | L1 (mm) | S1 | |
| PAY 306 HS | 6 | 4 | 1/4" | M 18 x 1.5 | 10 | 65,0 | 19 | |
| PAY 308 HS | 8 | 5 | 5/16" | M 20 x 1.5 | 12 | 62,0 | 22 | |
| PAY 310 HS | 10 | 6 | 3/8" | M 22 x 1.5 | 14 | 71,0 | 22 | |
| PAY 313 HS | 12 | 8 | 1/2" | M 24 x 1.5 | 16 | 74,0 | 24 | |
| PAY 316 HS | 16 | 10 | 5/8" | M 30 x 2 | 20 | 88,0 | 30 | |
| PAY 320 HS | 19 | 12 | 3/4" | M 36 x 2 | 25 | 90,0 | 36 | |
| PAY 325 HS | 25 | 16 | 1" | M 42 x 2 | 30 | 92,0 | 46 | |