
## **PAY 300 SF 45**

Swage fitting, SFL angle 45°



| Properties      |                                |  |  |  |  |  |
|-----------------|--------------------------------|--|--|--|--|--|
| Connection 1    | SAE flange connection 3000 PSI |  |  |  |  |  |
| Sealing form 1  | flat seal with SF O-ring       |  |  |  |  |  |
| Short code      | SFL                            |  |  |  |  |  |
| Standard        | SAE J518<br>ISO 6162-1         |  |  |  |  |  |
| Scope of supply | Swage nipple + swage ferrule   |  |  |  |  |  |
| Material        | Steel                          |  |  |  |  |  |
| Surface         | electro galvanised             |  |  |  |  |  |





| DN | Size     | Inches         | Flange size            | D                              | Н  | L1  | L2  |
|----|----------|----------------|------------------------|--------------------------------|--|---|---|
|    |          |                |                        | (mm)                           | (mm)   | (mm)  | (mm)  |
| 16 | 10       | 5/8"           | 3/4"                   | 38,1                           | 6,7  | 113,5   | 24,0  |
| 25 | 16       | 1"             | 1"                     | 44,4                           | 8,0  | 125,0   | 32,0  |
| 31 | 20       | 1.1/4"         | 1.1/4"                 | 50,8                           | 8,0  | 174,0   | 37,0  |
|    | 16<br>25 | 16 10<br>25 16 | 16 10 5/8"<br>25 16 1" | 16 10 5/8" 3/4"<br>25 16 1" 1" | (mm)   16 10 5/8" 3/4" 38,1   25 16 1" 1" 44,4 | (mm) (mm)   16 10 5/8" 3/4" 38,1 6,7   25 16 1" 1" 44,4 8,0 | 16 10 5/8" 3/4" 38,1 6,7 113,5   25 16 1" 1" 44,4 8,0 125,0 |