

PN AB 90 VA

Swage nipple, DKR angle 90°

HANSA FLEX

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	BSP nut thread
Sealing form 1	60° outer cone
Short code	DKR
Standard	ISO 8434-6 BS 5200
Material	Stainless steel



Note

Choose the appropriate ferrule based on the hose type.

Item	Identification	DN	Size	Inches	Operating pressure (bar)	G1	L2 (mm)	S1
	PN 06 AB 02 90 VA	6	4	1/4"	350,0	G 1/8" -28	30,0	14
	PN 06 AB 90 VA	6	4	1/4"	400,0	G 1/4" -19	28,0	17
	PN 06 AB 10 90 VA	6	4	1/4"	400,0	G 3/8" -19	26,0	19
	PN 08 AB 10 90 VA	8	5	5/16"	400,0	G 3/8" -19	34,0	19
	PN 10 AB 06 90 VA	10	6	3/8"	400,0	G 1/4" -19	39,0	19
	PN 10 AB 90 VA	10	6	3/8"	400,0	G 3/8" -19	34,0	19
	PN 10 AB 13 90 VA	10	6	3/8"	350,0	G 1/2" -14	42,5	27
	PN 13 AB 10 90 VA	12	8	1/2"	350,0	G 3/8" -19	47,5	22
	PN 13 AB 90 VA	12	8	1/2"	350,0	G 1/2" -14	42,5	27
	PN 13 AB 16 90 VA	12	8	1/2"	350,0	G 5/8" -14	50,5	27
	PN 13 AB 20 90 VA	12	8	1/2"	315,0	G 3/4" -14	43,0	32
	PN 16 AB 90 VA	16	10	5/8"	350,0	G 5/8" -14	54,0	27
	PN 16 AB 20 90 VA	16	10	5/8"	315,0	G 3/4" -14	54,0	32
	PN 20 AB 90 VA	19	12	3/4"	315,0	G 3/4" -14	54,0	32
	PN 20 AB 25 90 VA	19	12	3/4"	250,0	G 1" -11	69,0	41
	PN 25 AB 90 VA	25	16	1"	250,0	G 1" -11	69,0	41
	PN 25 AB 32 90 VA	25	16	1"	160,0	G 1.1/4" -11	81,0	50
	PN 32 AB 90 VA	31	20	1.1/4"	160,0	G 1.1/4" -11	81,0	50
	PN 32 AB 40 90 VA	31	20	1.1/4"	125,0	G 1.1/2" -11	103,0	55
	PN 40 AB 90 VA	38	24	1.1/2"	125,0	G 1.1/2" -11	102,0	55
	PN 40 AB 50 90 VA	38	24	1.1/2"	80,0	G 2" -11	-	70
	PN 50 AB 90 VA	51	32	2"	80,0	G 2" -11	133,0	70

Product versions

PN AB 90 Swage nipple, DKR angle 90°, Steel