

PN AF 45

Swage nipple, DKF angle 45°

HANSA FLEX

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	metric nut thread
Sealing form 1	24° outer cone for French series imperial pipe.
Short code	DKF
Series	French (imperial pipe - series gas)
Material	Steel
Surface	electro galvanised



Note

Choose the appropriate ferrule based on the hose type.

Item

Identification	DN	Size	Inches	Operating pressure (bar)	G1	for external pipe Ø mm	L1 (mm)	L2 (mm)	S1
PN 08 AF 10 45	8	5	5/16"	400,0	M 20 x 1.5	13,25	92,0	25,0	24
PN 10 AF 45	10	6	3/8"	400,0	M 20 x 1.5	13,25	91,0	25,0	24
PN 10 AF 13 45	10	6	3/8"	250,0	M 24 x 1.5	16,75	100,0	28,0	30
PN 13 AF 45	12	8	1/2"	250,0	M 24 x 1.5	16,75	98,0	28,0	30
PN 13 AF 16 45	12	8	1/2"	250,0	M 30 x 1.5	21,26	89,0	21,0	36
PN 16 AF 45	16	10	5/8"	250,0	M 30 x 1.5	21,26	94,0	21,0	36
PN 20 AF 45	19	12	3/4"	250,0	M 36 x 1.5	26,75	123,0	33,0	41
PN 25 AF 45	25	16	1"	160,0	M 45 x 1.5	33,50	150,0	41,0	55