


PN AF 90

Swage nipple, DKF angle 90°

HANSA FLEX

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	metric nut thread
Sealing form 1	24° outer cone for French series imperial pipe.
Short code	DKF
Series	French (imperial pipe - series gas)
Material	Steel
Surface	electro galvanised



Note

Choose the appropriate ferrule based on the hose type.

Item

Identification	DN	Size	Inches	Operating pressure (bar)	G1	for external pipe Ø mm	L1 (mm)	L2 (mm)	S1
PN 08 AF 10 90	8	5	5/16"	400,0	M 20 x 1.5	13,25	74,0	42,0	24
PN 10 AF 90	10	6	3/8"	400,0	M 20 x 1.5	13,25	73,0	42,0	24
PN 10 AF 13 90	10	6	3/8"	250,0	M 24 x 1.5	16,75	89,0	56,0	30
PN 13 AF 90	12	8	1/2"	250,0	M 24 x 1.5	16,75	88,0	56,0	30
PN 13 AF 16 90	12	8	1/2"	250,0	M 30 x 1.5	21,26	87,0	57,0	37
PN 16 AF 90	16	10	5/8"	250,0	M 30 x 1.5	21,26	91,0	57,0	36
PN 20 AF 90	19	12	3/4"	250,0	M 36 x 1.5	26,75	109,0	66,0	41
PN 25 AF 90	25	16	1"	160,0	M 45 x 1.5	33,50	125,0	75,0	55