


PN AFL VA

Swage nipple, DKL

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	metric nut thread
Sealing form 1	24°/60° Universal sealing head
Short code	DKL
Series	light
Material	Stainless steel



Note

Choose the appropriate ferrule based on the hose type.

Item

Identification	DN	Size	Inches	Operating pressure (bar)	G1	for external pipe Ø (mm)	L1 (mm)	S1
PN 06 AFL 04 VA	6	4	1/4"	250,0	M 12 x 1.5	6	49,8	14
PN 06 AFL VA	6	4	1/4"	250,0	M 14 x 1.5	8	50,8	17
PN 06 AFL 08 VA	6	4	1/4"	250,0	M 16 x 1.5	10	50,8	19
PN 08 AFL 06 VA	8	5	5/16"	250,0	M 16 x 1.5	8	51,8	17
PN 08 AFL VA	8	5	5/16"	250,0	M 16 x 1.5	10	51,8	19
PN 08 AFL 10 VA	8	5	5/16"	250,0	M 18 x 1.5	12	51,8	22
PN 10 AFL 08 VA	10	6	3/8"	250,0	M 16 x 1.5	10	52,8	19
PN 10 AFL VA	10	6	3/8"	250,0	M 18 x 1.5	12	52,8	22
PN 13 AFL VA	12	8	1/2"	250,0	M 22 x 1.5	15	55,3	27
PN 16 AFL VA	16	10	5/8"	160,0	M 26 x 1.5	18	59,5	32
PN 20 AFL VA	19	12	3/4"	160,0	M 30 x 2	22	66,0	36
PN 25 AFL VA	25	16	1"	100,0	M 36 x 2	28	73,5	41
PN 32 AFL VA	31	20	1.1/4"	100,0	M 45 x 2	35	95,0	50
PN 40 AFL VA	38	24	1.1/2"	100,0	M 52 x 2	42	95,0	60

Product versions

PN AFL	Swage nipple, DKL, Steel
--------	--------------------------