


# PN AJF 90

Swage nipple, ORFS angle 90°

## Properties

<b>Application</b>	Swage nipple for HD 100 to HD 400, KP and TE hoses
<b>Connection 1</b>	UN/UNF nut threads
<b>Sealing form 1</b>	flat sealing
<b>Short code</b>	ORFS
<b>Standard</b>	ISO 8434-3
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Note

Choose the appropriate ferrule based on the hose type.

## Item

Identification	DN	Size	Inches	Operating pressure (bar)	G1	L1 (mm)	L2 (mm)	S1
PN 06 AJF 90	6	4	1/4"	413,0	9/16"-18 UNF	55,0	26,5	17
PN 06 AJF 90 L21	6	4	1/4"	413,0	9/16"-18 UNF	55,0	21,0	17
PN 06 AJF 90 L58	6	4	1/4"	413,0	9/16"-18 UNF	55,0	58,0	17
PN 06 AJF 10 90	6	4	1/4"	413,0	11/16"-16 UN	55,0	28,0	22
PN 08 AJF 10 90	8	5	5/16"	413,0	11/16"-16 UN	58,0	28,0	22
PN 08 AJF 10 90 L23	8	5	5/16"	413,0	11/16"-16 UN	58,0	23,0	22
PN 10 AJF 90	10	6	3/8"	413,0	11/16"-16 UN	64,0	32,0	22
PN 10 AJF 90 L23	10	6	3/8"	413,0	11/16"-16 UN	64,0	23,0	22
PN 10 AJF 90 L 69	10	6	3/8"	413,0	11/16"-16 UN	64,0	69,0	22
PN 10 AJF 13 90	10	6	3/8"	413,0	13/16"-16 UN	64,0	33,0	24
PN 13 AJF 10 90 L30	12	8	1/2"	413,0	11/16"-16 UN	72,5	30,0	22
PN 13 AJF 90	12	8	1/2"	413,0	13/16"-16 UN	72,5	37,0	24
PN 13 AJF 90 L29	12	8	1/2"	413,0	13/16"-16 UN	72,5	29,0	24
PN 13 AJF 90 L82	12	8	1/2"	413,0	13/16"-16 UN	72,5	82,0	24
PN 13 AJF 16 90	12	8	1/2"	413,0	1" -14 UNS	72,5	41,0	30
PN 13 AJF 20 90	12	8	1/2"	413,0	1.3/16" -12 UN	71,5	43,5	36
PN 13 AJF 20 90 L38	12	8	1/2"	413,0	1.3/16" -12 UN	72,5	38,0	36
PN 16 AJF 90	16	10	5/8"	413,0	1" -14 UNS	88,0	47,5	30
PN 16 AJF 90 L32	16	10	5/8"	413,0	1" -14 UNS	88,0	32,0	30
PN 16 AJF 90 L94	16	10	5/8"	413,0	1" -14 UNS	88,0	94,0	30
PN 16 AJF 20 90	16	10	5/8"	413,0	1.3/16" -12 UN	89,5	49,0	36
PN 20 AJF 90	19	12	3/4"	413,0	1.3/16" -12 UN	99,5	52,0	36
PN 20 AJF 90 L48	19	12	3/4"	413,0	1.3/16" -12 UN	99,5	48,0	36
PN 20 AJF 90 L96	19	12	3/4"	413,0	1.3/16" -12 UN	99,5	96,0	36
PN 20 AJF 25 90	19	12	3/4"	413,0	1.7/16" -12 UN	98,5	56,0	41
PN 25 AJF 20 90 L51	25	16	1"	413,0	1.3/16" -12 UN	127,0	51,0	36
PN 25 AJF 90	25	16	1"	413,0	1.7/16" -12 UN	127,0	63,5	41
PN 25 AJF 90 L56	25	16	1"	413,0	1.7/16" -12 UN	127,0	56,0	41
PN 25 AJF 90 L114	25	16	1"	413,0	1.7/16" -12 UN	127,0	114,0	41
PN 32 AJF 90	31	20	1.1/4"	275,0	1.11/16" -12 UN	151,5	76,0	50
PN 32 AJF 90 L129	31	20	1.1/4"	275,0	1.11/16" -12 UN	151,5	129,0	50
PN 40 AJF 90	38	24	1.1/2"	275,0	2" -12 UN	176,5	89,0	60
PN 40 AJF 90 L146	38	24	1.1/2"	275,0	2" -12 UN	176,5	146,0	60