


PN B VA

Swage nipple, RGN

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	Banjo for metric hollow screw
Sealing form 1	Sealed by copper ring
Short code	RGN
Standard	DIN 7642
Material	Stainless steel



Note

Choose the appropriate ferrule based on the hose type.

Item

Identification	DN	Size	Inches	Operating pressure (bar)	D1 (mm)	for hollow screw
PN 06 B 04 VA	6	4	1/4"	200,0	10,1	M 10
PN 06 B VA	6	4	1/4"	200,0	12,1	M 12
PN 06 B 08 VA	6	4	1/4"	200,0	14,1	M 14
PN 08 B 04 VA	8	5	5/16"	200,0	10,1	M 10
PN 08 B 06 VA	8	5	5/16"	200,0	12,1	M 12
PN 08 B VA	8	5	5/16"	200,0	14,1	M 14
PN 08 B 10 VA	8	5	5/16"	200,0	16,1	M 16
PN 10 B 08 VA	10	6	3/8"	200,0	14,1	M 14
PN 10 B VA	10	6	3/8"	200,0	16,1	M 16
PN 10 B 13 VA	10	6	3/8"	200,0	18,1	M 18
PN 13 B 10 VA	12	8	1/2"	200,0	16,1	M 16
PN 13 B VA	12	8	1/2"	200,0	18,1	M 18
PN 13 B 16 VA	12	8	1/2"	200,0	22,1	M 22
PN 16 B VA	16	10	5/8"	200,0	22,1	M 22
PN 20 B VA	19	12	3/4"	200,0	26,1	M 26