
PN FS 45 VA

Swage nipple, BES angle 45°

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	Pipe sockets
Sealing form 1	Cutting ring connection
Short code	BES
Standard	ISO 8434-1
Series	heavy
Material	Stainless steel





Note

Final cutting ring assembly must be carried out in the hardened pre-assembly socket (VOM...).
Choose the appropriate ferrule based on the hose type.
Do not use for new designs; we recommend: PN...AOS...45 VA.

Item

Identification	DN	Size	Inches	D2 (mm)	L2 (mm)
PN 06 FS 03 45 VA	6	4	1/4"	6,0	22,0
PN 06 FS 04 45 VA	6	4	1/4"	8,0	22,0
PN 06 FS 45 VA	6	4	1/4"	10,0	22,5
PN 08 FS 06 45 VA	8	5	5/16"	10,0	25,0
PN 08 FS 45 VA	8	5	5/16"	12,0	24,0
PN 10 FS 06 45 VA	10	6	3/8"	10,0	25,0
PN 10 FS 08 45 VA	10	6	3/8"	12,0	45,0
PN 10 FS 45 VA	10	6	3/8"	14,0	-
PN 13 FS 45 VA	12	8	1/2"	16,0	32,0
PN 16 FS 45 VA	16	10	5/8"	20,0	31,0
PN 20 FS 45 VA	19	12	3/4"	25,0	42,0
PN 25 FS 45 VA	25	16	1"	30,0	-
PN 32 FS 45 VA	31	20	1.1/4"	38,0	-

Product versions

PN FS 45	Swage nipple, BES angle 45°, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.