
PN FS VA
Swage nipple, BES

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	Pipe sockets
Sealing form 1	Cutting ring connection
Short code	BES
Standard	ISO 8434-1
Series	heavy
Material	Stainless steel





Note

Final cutting ring assembly must be carried out in the hardened pre-assembly socket (VOM...).
Choose the appropriate ferrule based on the hose type.
Do not use for new designs; we recommend: PN...AOS...VA.

Item

Identification	DN	Size	Inches	Operating pressure (bar)	D2 (mm)	L1 (mm)
PN 06 FS 03 VA	6	4	1/4"	630,0	6,0	58,3
PN 06 FS 04 VA	6	4	1/4"	630,0	8,0	60,8
PN 06 FS VA	6	4	1/4"	630,0	10,0	63,3
PN 06 FS 08 VA	6	4	1/4"	630,0	12,0	65,3
PN 08 FS 04 VA	8	5	5/16"	630,0	8,0	60,8
PN 08 FS 06 VA	8	5	5/16"	630,0	10,0	61,3
PN 08 FS VA	8	5	5/16"	630,0	12,0	65,3
PN 10 FS 06 VA	10	6	3/8"	630,0	10,0	63,8
PN 10 FS 08 VA	10	6	3/8"	630,0	12,0	63,8
PN 10 FS VA	10	6	3/8"	630,0	14,0	65,3
PN 13 FS 08 VA	12	8	1/2"	400,0	12,0	65,8
PN 13 FS VA	12	8	1/2"	400,0	16,0	70,3
PN 13 FS 16 VA	12	8	1/2"	400,0	20,0	73,8
PN 16 FS VA	16	10	5/8"	400,0	20,0	79,0
PN 20 FS 16 VA	19	12	3/4"	400,0	20,0	80,0
PN 20 FS VA	19	12	3/4"	400,0	25,0	88,0
PN 25 FS 20 VA	25	16	1"	250,0	25,0	88,5
PN 25 FS VA	25	16	1"	250,0	30,0	98,5
PN 32 FS VA	31	20	1.1/4"	250,0	38,0	124,0

Product versions

PN FS	Swage nipple, BES, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.