
PN SF 90 VA

Swage nipple, SFL angle 90°

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	SAE flange connection 3000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFL
Standard	SAE J518 ISO 6162-1
Material	Stainless steel





Note

Choose the appropriate ferrule based on the hose type.

Ordering information

Seals of NBR

FPM (Viton) on request

Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)	L2 (mm)
PN 13 SF 90 VA	12	8	1/2"	1/2"	350,0	30,2	6,7	54,0
PN 13 SF 20 90 VA	12	8	1/2"	3/4"	350,0	38,1	6,7	61,0
PN 16 SF 13 90 VA	16	10	5/8"	1/2"	350,0	30,2	6,7	60,0
PN 16 SF 20 90 VA	16	10	5/8"	3/4"	350,0	38,1	6,7	61,0
PN 20 SF 90 VA	19	12	3/4"	3/4"	350,0	38,1	6,7	68,0
PN 20 SF 25 90 VA	19	12	3/4"	1"	320,0	44,5	8,0	73,0
PN 25 SF 90 VA	25	16	1"	1"	320,0	44,5	8,0	77,0
PN 25 SF 32 90 VA	25	16	1"	1.1/4"	280,0	50,8	8,0	89,0
PN 32 SF 90 VA	31	20	1.1/4"	1.1/4"	280,0	50,8	8,0	92,0
PN 32 SF 40 90 VA	31	20	1.1/4"	1.1/2"	210,0	60,3	8,0	92,5
PN 40 SF 90 VA	38	24	1.1/2"	1.1/2"	210,0	60,3	8,0	104,0
PN 40 SF 50 90 VA	38	24	1.1/2"	2"	210,0	71,4	9,5	120,0
PN 50 SF 90 VA	51	32	2"	2"	210,0	71,4	9,5	144,0
PN 60 SF 90 VA	60	40	2.3/8"	2.1/2"	175,0	84,1	9,5	-

Product versions

PN SF 90	Swage nipple, SFL angle 90°, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.