


# PN SF 90 VA

Swage nipple, SFL angle 90°

**HANSA FLEX**

## Properties

<b>Application</b>	Swage nipple for HD 100 to HD 400, KP and TE hoses
<b>Connection 1</b>	SAE flange connection 3000 PSI
<b>Sealing form 1</b>	flat seal with SF O-ring
<b>Short code</b>	SFL
<b>Standard</b>	SAE J518 ISO 6162-1
<b>Material</b>	Stainless steel



## Note

Choose the appropriate ferrule based on the hose type.

## Ordering information

Seals of NBR

FPM (Viton) on request

## Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)	L2 (mm)
PN 13 SF 90 VA	12	8	1/2"	1/2"	350,0	30,2	6,7	54,0
PN 13 SF 20 90 VA	12	8	1/2"	3/4"	350,0	38,1	6,7	61,0
PN 16 SF 13 90 VA	16	10	5/8"	1/2"	350,0	30,2	6,7	60,0
PN 16 SF 20 90 VA	16	10	5/8"	3/4"	350,0	38,1	6,7	61,0
PN 20 SF 90 VA	19	12	3/4"	3/4"	350,0	38,1	6,7	68,0
PN 20 SF 25 90 VA	19	12	3/4"	1"	320,0	44,5	8,0	73,0
PN 25 SF 90 VA	25	16	1"	1"	320,0	44,5	8,0	77,0
PN 25 SF 32 90 VA	25	16	1"	1.1/4"	280,0	50,8	8,0	89,0
PN 32 SF 90 VA	31	20	1.1/4"	1.1/4"	280,0	50,8	8,0	92,0
PN 32 SF 40 90 VA	31	20	1.1/4"	1.1/2"	210,0	60,3	8,0	92,5
PN 40 SF 90 VA	38	24	1.1/2"	1.1/2"	210,0	60,3	8,0	104,0
PN 40 SF 50 90 VA	38	24	1.1/2"	2"	210,0	71,4	9,5	120,0
PN 50 SF 90 VA	51	32	2"	2"	210,0	71,4	9,5	144,0
PN 60 SF 90 VA	60	40	2.3/8"	2.1/2"	175,0	84,1	9,5	-

## Product versions

PN SF 90 Swage nipple, SFL angle 90°, Steel