

PN SF9

Swage nipple, SFS-CAT

Properties

| | |
|-----------------------|--|
| Application | Swage nipple for HD 100 to HD 400, KP and TE hoses |
| Connection 1 | SAE flange connection 6000 PSI |
| Sealing form 1 | flat seal with SF O-ring |
| Short code | SFS-CAT |
| suitable for | Caterpillar |
| Material | Steel |
| Surface | electro galvanised |



Note

Choose the appropriate ferrule based on the hose type.

Item

| Identification | DN | Size | Inches | Flange size | Operating pressure (bar) | D (mm) | H (mm) | L1 (mm) |
|----------------|----|------|--------|-------------|--------------------------|--------|--------|---------|
| PN 20 SF9 | 19 | 12 | 3/4" | 3/4" | 420,0 | 41,3 | 14,6 | 110,0 |
| PN 20 SF9 25 | 19 | 12 | 3/4" | 1" | 420,0 | 47,6 | 14,6 | 114,5 |
| PN 25 SF9 | 25 | 16 | 1" | 1" | 420,0 | 47,6 | 14,6 | 127,0 |
| PN 25 SF9 32 | 25 | 16 | 1" | 1.1/4" | 420,0 | 54,0 | 14,6 | 131,5 |
| PN 32 SF9 | 31 | 20 | 1.1/4" | 1.1/4" | 420,0 | 54,0 | 14,6 | 143,5 |
| PN 32 SF9 40 | 31 | 20 | 1.1/4" | 1.1/2" | 420,0 | 63,5 | 14,6 | 148,0 |
| PN 40 SF9 | 38 | 24 | 1.1/2" | 1.1/2" | 420,0 | 63,5 | 14,6 | 156,0 |