


PN WEO S 90

Swage nipple, WEO S angle 90°

HANSA**FLEX**

Properties

Application	Swage nipple for HD 100 to HD 400, KP and TE hoses
Connection 1	WEO plug
Sealing form 1	O-ring sealed pin
Material	Steel
Surface	electro galvanised



Note

Choose the appropriate ferrule based on the hose type.

Description

Self-aligning to prevent torsional stress.

Item

Identification	DN	Size	Inches	Operating pressure	Size	Ø D1 (mm)	L2 (mm)
PN 06 WEO 10 S 90	6	4	1/4"	PN 350	1/4"	10,0	48,5
PN 06 WEO 13 S 90	6	4	1/4"	PN 350	3/8"	13,0	54,0
PN 08 WEO 13 S 90	8	5	5/16"	PN 350	3/8"	13,0	58,0
PN 10 WEO 13 S 90	10	6	3/8"	PN 350	3/8"	13,0	58,0
PN 10 WEO 16 S 90	10	6	3/8"	PN 350	1/2"	16,0	59,5
PN 13 WEO 16 S 90	12	8	1/2"	PN 350	1/2"	16,0	68,0
PN 13 WEO 23 S 90	12	8	1/2"	PN 350	3/4"	23,0	82,0
PN 16 WEO 23 S 90	16	10	5/8"	PN 350	3/4"	23,0	100,0
PN 20 WEO 23 S 90	19	12	3/4"	PN 350	3/4"	23,0	100,0

Spare parts

WEO S DEMORING	WEO disassembly ring
WEO S M ANSCHLAG	WEO fitting stop