

# L AB HB

Screw-on socket, L shaped

**HANSA FLEX**

## Properties

<b>Connection 1</b>	BSP nut thread
<b>Sealing form 1</b>	60° outer cone
<b>Connection 2 + 3</b>	BSP cylindrical external threads
<b>Sealing form 2 + 3</b>	60° inner cone
<b>Design</b>	Adjustable direction screw-on socket
<b>Construction</b>	L shaped
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	G1	G2 + G3	AF (mm)	S1
<b>L AB 04 HB</b>	G 1/4" -19	G 1/4" -19	14	19
<b>L AB 06 HB</b>	G 3/8" -19	G 3/8" -19	17	22
<b>L AB 08 HB</b>	G 1/2" -14	G 1/2" -14	22	27
<b>L AB 10 HB</b>	G 5/8" -14	G 5/8" -14	24	30
<b>L AB 12 HB</b>	G 3/4" -14	G 3/4" -14	27	32
<b>L AB 16 HB</b>	G 1" -11	G 1" -11	36	41
<b>L AB 20 HB</b>	G 1.1/4" -11	G 1.1/4" -11	46	50
<b>L AB 24 HB</b>	G 1.1/2" -11	G 1.1/2" -11	50	55
<b>L AB 32 HB</b>	G 2" -11	G 2" -11	60	70

SW, S1, S2 = With across flats

## Product versions

**L AB HB VA** Screw-on socket, L shaped, Stainless steel