

# L O HJ

Screw-in socket, L shaped

**HANSA FLEX**

## Properties

|                           |                                      |
|---------------------------|--------------------------------------|
| <b>Connection 1</b>       | UN/UNF external threads              |
| <b>Sealing form 1</b>     | O-ring seal on screw-in socket       |
| <b>Connection 2 + 3</b>   | UN/UNF external threads              |
| <b>Sealing form 2 + 3</b> | 74° outer cone                       |
| <b>Design</b>             | Adjustable direction screw-in socket |
| <b>Construction</b>       | L shaped                             |
| <b>Material</b>           | Steel                                |
| <b>Surface</b>            | electro galvanised                   |



## Item

| Identification | G1             | G2 + G3        | AF<br>(mm) | S1 | OR           |
|----------------|----------------|----------------|------------|----|--------------|
| L O 04 HJ      | 7/16"-20 UNF   | 7/16"-20 UNF   | 11         | 14 | 8.92 x 1.83  |
| L O 05 HJ      | 1/2"-20 UNF    | 1/2"-20 UNF    | 14         | 16 | 10.52 x 1.83 |
| L O 06 HJ      | 9/16"-18 UNF   | 9/16"-18 UNF   | 14         | 17 | 15.40 x 2.10 |
| L O 08 HJ      | 3/4"-16 UNF    | 3/4"-16 UNF    | 19         | 22 | 16.36 x 2.20 |
| L O 08 HJ 06   | 3/4"-16 UNF    | 9/16"-18 UNF   | 19         | 22 | 16.36 x 2.20 |
| L O 10 HJ      | 7/8"-14 UNF    | 7/8"-14 UNF    | 22         | 25 | 19.18 x 2.46 |
| L O 10 HJ 12   | 7/8"-14 UNF    | 1.1/16" -12 UN | 27         | 25 | 19.18 x 2.46 |
| L O 12 HJ      | 1.1/16" -12 UN | 1.1/16" -12 UN | 27         | 32 | 23.47 x 2.95 |
| L O 12 HJ 16   | 1.1/16" -12 UN | 1.5/16" -12 UN | 33         | 32 | 23.47 x 2.95 |
| L O 16 HJ      | 1.5/16" -12 UN | 1.5/16" -12 UN | 33         | 38 | 29.74 x 2.95 |
| L O 16 HJ 12   | 1.5/16" -12 UN | 1.1/16" -12 UN | 27         | 38 | 29.74 x 2.95 |
| L O 20 HJ      | 1.5/8" -12 UN  | 1.5/8" -12 UN  | 41         | 48 | 37.47 x 3.00 |
| L O 24 HJ      | 1.7/8" -12 UN  | 1.7/8" -12 UN  | 48         | 54 | 43.69 x 3.00 |

AF = Width across flats

## Product versions

L O HJ VA Screw-in socket, L shaped, Stainless steel