

# L O HJOF VA

Screw-in socket, L shaped

## Properties

<b>Connection 1</b>	UN/UNF external threads
<b>Sealing form 1</b>	Shape F
<b>Connection 2 + 3</b>	ORFS external threads
<b>Sealing form 2 + 3</b>	flat seal with O-ring
<b>Design</b>	Adjustable direction screw-in socket
<b>Construction</b>	L shaped
<b>Material</b>	Stainless steel



## Ordering information

Seals of NBR  
FPM (Viton) on request

## Item

Identification	G1	G2 + G3	AF (mm)	S1	OR1	OR2 + OR3
<b>L O 04 HJOF VA</b>	7/16"-20 UNF	9/16"-18 UNF	14	16	8.92 x 1.83	7.66 x 1.78
<b>L O 06 HJOF VA</b>	9/16"-18 UNF	11/16" -16 UN	19	19	11.89 x 1.98	9.25 x 1.78
<b>L O 08 HJOF VA</b>	3/4"-16 UNF	13/16" -16 UN	19	24	16.36 x 2.21	12.42 x 1.78
<b>L O 10 HJOF VA</b>	7/8" -14 UNF	1" -14 UNS	27	27	19.18 x 2.46	15.60 x 1.78
<b>L O 12 HJOF VA</b>	1.1/16" -12 UN	1.3/16" -12 UN	30	35	23.47 x 2.95	18.77 x 1.78
<b>L O 16 HJOF VA</b>	1.5/16" -12 UN	1.7/16" -12 UN	36	41	29.74 x 2.95	23.52 x 1.78

AF = Width across flats

## Product versions

**L O HJOF** Screw-in socket, L shaped, Steel