T AB HB VA Screw-on socket, T shaped

HANSA/FLEX

Properties

Fioperties			
Connection 1	BSP nut thread		
Sealing form 1	60° outer cone		
Connection 2 + 3	BSP cylindrical external threads		
Sealing form 2 + 3	60° inner cone		
Design	Adjustable direction screw-on socket		
Construction	T shaped		
Material	Stainless steel		





Item

G1	G2 + G3	AF	S1
		(mm)	
G 1/8" -28	G 1/8" -28	12	14
G 1/4" -19	G 1/4" -19	14	19
G 3/8" -19	G 3/8" -19	17	22
G 1/2" -14	G 1/2" -14	19	27
G 3/4" -14	G 3/4" -14	27	32
G 1" -11	G 1" -11	36	41
G 1.1/4" -11	G 1.1/4" -11	41	50
G 1.1/2" -11	G 1.1/2" -11	50	55
	G 1/8" -28 G 1/4" -19 G 3/8" -19 G 1/2" -14 G 3/4" -14 G 1" -11 G 1.1/4" -11	G 1/8" -28 G 1/8" -28 G 1/4" -19 G 1/4" -19 G 3/8" -19 G 3/8" -19 G 1/2" -14 G 1/2" -14 G 3/4" -14 G 3/4" -14 G 1" -11 G 1" -11 G 1.1/4" -11 G 1.1/4" -11	G 1/8" -28 G 1/8" -28 12 G 1/4" -19 G 1/4" -19 14 G 3/8" -19 G 3/8" -19 17 G 1/2" -14 G 1/2" -14 19 G 3/4" -14 G 3/4" -14 27 G 1" -11 G 1" -11 36 G 1.1/4" -11 G 1.1/4" -11 41

SW, S1, S2 = With across flats

Product versions

T AB HB Screw-on socket, T shaped, Steel