


Properties					
Connection 1	BSP nut thread				
Sealing form 1	60° outer cone				
Connection 2 + 3	BSP cylindrical external threads				
Sealing form 2 + 3	60° inner cone				
Design	Adjustable direction screw-on socket				
Construction	T shaped				
Material	Stainless steel				





Item				
Identification	G1	G2 + G3	AF (mm)	S1
T AB 02 HB VA	G 1/8" -28	G 1/8" -28	12	14
T AB 04 HB VA	G 1/4" -19	G 1/4" -19	14	19
T AB 06 HB VA	G 3/8" -19	G 3/8" -19	17	22
T AB 08 HB VA	G 1/2" -14	G 1/2" -14	19	27
T AB 12 HB VA	G 3/4" -14	G 3/4" -14	27	32
T AB 16 HB VA	G 1" -11	G 1" -11	36	41
T AB 20 HB VA	G 1.1/4" -11	G 1.1/4" -11	41	50
T AB 24 HB VA	G 1.1/2" -11	G 1.1/2" -11	50	55

SW, S1, S2 = With across flats

_				- 4					
Ю	ra	М		at.	ve	re	in	n	0
	ıv	u	u	υL	vc	13	ıu	ш	3

T AB HB Screw-on socket, T shaped, Steel