


# T HROK HJOF

Screw-in socket, T shaped

## Properties

<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	Thread socket with O-ring + spacer diaphragm ring
<b>Connection 2 + 3</b>	ORFS external threads
<b>Sealing form 2 + 3</b>	flat seal with O-ring
<b>Design</b>	Adjustable direction screw-in socket
<b>Construction</b>	T shaped
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	G1	G2 + G3	AF (mm)	S1	OR1	OR2 + OR3
<b>T HROK 02 HJOF 04</b>	G 1/8" -28	9/16"-18 UNF	14	14	8.00 x 2.00	7.65 x 1.78
<b>T HROK 04 HJOF</b>	G 1/4" -19	9/16"-18 UNF	19	19	10.77 x 2.62	7.65 x 1.78
<b>T HROK 04 HJOF 06</b>	G 1/4" -19	11/16" -16 UN	19	19	10.70 x 2.62	9.25 x 1.78
<b>T HROK 06 HJOF</b>	G 3/8" -19	11/16" -16 UN	19	22	13.94 x 2.62	9.25 x 1.78
<b>T HROK 06 HJOF 08</b>	G 3/8" -19	13/16" -16 UN	19	22	13.94 x 2.62	12.42 x 1.78
<b>T HROK 08 HJOF</b>	G 1/2" -14	13/16" -16 UN	27	27	17.86 x 2.62	12.42 x 1.78
<b>T HROK 08 HJOF 10</b>	G 1/2" -14	1" -14 UNS	27	27	17.86 x 2.62	15.60 x 1.78
<b>T HROK 12 HJOF 10</b>	G 3/4" -14	1" -14 UNS	30	36	23.47 x 2.62	15.60 x 1.78
<b>T HROK 12 HJOF</b>	G 3/4" -14	1.3/16" -12 UN	30	36	23.47 x 2.62	12.42 x 1.78
<b>T HROK 16 HJOF</b>	G 1" -11	1.7/16" -12 UN	36	41	29.75 x 3.53	23.52 x 1.78
<b>T HROK 20 HJOF</b>	G 1.1/4" -11	1.11/16" -12 UN	41	50	37.69 x 3.53	29.87 x 1.78
<b>T HROK 24 HJOF</b>	G 1.1/2" -11	2" -12 UN	50	55	44.04 x 3.53	37.82 x 1.78

SW, S1, S2 = With across flats

## Spare parts

**KAMRING G** Spacer diaphragm ring, imperial